Data sheet Cisco public



Cisco Webex Room Kit Plus Precision 60 Integrator Package

Contents

Cisco Webex Room Kit Plus Precision 6o features and benefits	3
Cisco Webex registration	4
Product specifications	4
Ordering information	7
Warranty information	9
Cisco environmental sustainability	10
Cisco Services and Support	10
Cisco Capital	10
For more information	10

The Cisco Webex[™] Room Kit Plus Precision 6o (Room Kit Plus P6o) integrator package is a powerful collaboration solution that integrates with flat panel displays to bring more intelligence and versatility to your collaboration spaces. This package combines the performance of the Cisco Webex Room Kit Plus codec (Codec Plus) and the flexibility of the Cisco Precision 6o Camera to offer maximum flexibility in scenarios where you need special camera placement, objects close up, or wide pan/tilt/zoom capability.

Package overview

The Room Kit Plus P60 integrator package delivers an unmatched audio and video experience that customers have come to expect from Cisco. In addition, the package provides flexibility for rooms that can benefit from a pan-tilt-zoom camera. The Precision 60 Camera not only delivers a premier imaging experience with 10x optical and 20x total zoom power, but also offers a high level of flexibility for custom and specialized integrations. The Precision 60 Camera also supports superior adaptability to light conditions and delivers one of the best image qualities in the industry for large meeting rooms.

The Room Kit Plus P60 integrator package is rich in functionality and experience but is priced and designed to be easily scalable to all of your collaboration spaces – whether registered on the premises or to Cisco Webex in the cloud.



Figure 1.Cisco Webex Room Kit Plus Precision 60 integrator package

Cisco Webex Room Kit Plus Precision 6o features and benefits

Feature	Benefit
Smart meetings	 Powerful imaging with one motorized high-quality camera (10x optical or 20x total zoom) Easily controlled by the Cisco Touch 10 control unit or with a Cisco Webex Teams app-enabled device End-to-end security
Smart presentations	 Supports dual screens for video and content Supports dual content sources for local meetings 4K content sharing (local 30 fps, remote 5 fps) Wired or wireless content sharing
Smart integrations	 Automatic screen and display integration through HDMI Consumer Electronics Control (CEC) Supports Wi-Fi

Feature	Benefit
	In-room control: Control peripherals such as lights and blinds through the Touch 10
Built for cloud and premises	 Flexibility to register on the premises or to Cisco Webex in the cloud Hardware is optimized to run on a cloud platform, for great experiences in shared rooms and spaces with easy access to hosted conferences

Cisco Webex registration

License level	Term
Cisco Device Subscription	Monthly or 1-, 2-, 3-, 4-, or 5-year options

Product specifications

Table 1.Specifications

Specification	Description	
Software compatibility	Cisco Collaboration Endpoint Software Version 9.1.5 or later, or Cisco Webex Room OS	
Default components in Cisco Webex Room Kit Plus Precision 60	 Cisco Webex Codec Plus Cisco Precision 6o Camera Cisco Touch 1o control unit 	
Optional hardware components	Cisco Table Microphone 20, wall mount for Codec Plus, cables	
Bandwidth	Up to 6 Mbps point-to-point	
Minimum bandwidth for resolution/frame rate	H.264 • 720p30 from 768 kbps • 720p60 from 1152 kbps • 1080p30 from 1472 kbps • 1080p60 from 2560 kbps	
Firewall traversal	 Cisco Expressway[™] technology H.460.18, H.460.19 firewall traversal 	
Video standards	• H.264, H.265	
Video inputs	 One HDMI input supports formats up to maximum 1080p60 Two HDMI inputs support formats up to maximum 4K (3840 x 2160) at 30 fps including HD1080p60 Consumer Electronics Control (CEC) 2.0 	
Video outputs	 Two HDMI outputs support formats up to 3840 x 216op6o (4Kp6o) Live video resolutions (encode and decode) up to 1920 x 108op6o (HD108op) CEC 2.0 	
Audio standards	• G.711, G.722, G.722.1, G.729, AAC-LD, and Opus	
Audio features	 High-quality 20-kHz audio Subwoofer line out Prepared for inductive loop (line out) Automatic Gain Control (AGC) Automatic noise reduction 	

Specification	Description	
	Active lip synchronization	
Audio inputs	 Three microphones, 4-pin mini-jack Two audio in from HDMI 	
Audio outputs (external)	 1 line out mini-jack (stereo) (Codec Plus) 1 RCA output for subwoofer 1 HDMI outputs HDMI input #1 supports Audio Return Channel (ARC): Audio output to Quad Camera speakers 	
Dual stream	 H.239 (H.323) dual stream Binary Floor Control Protocol (BFCP) (Session Initiation Protocol [SIP]) dual stream Supports resolutions up to 3840 x 2160p5 (4Kp5) and 1080p30 	
Wireless sharing	 Cisco Webex Teams client (up to 3840 x 2160p5) Cisco Intelligent Proximity client (up to 1920 x 1080p5) 	
Multipoint support	• 4-way embedded SIP/H. ₃₂₃ conferencing capability with MultiSite option	
MultiSite features (embedded multipoint) (optional upgrade)	 Adaptive SIP/H.323 MultiSite 3-way resolution up to 1080p30 + content up to 4Kp5 4-way resolution up to 720p30 + content up to 4Kp5 Full individual audio and video transcoding H.323/SIP/VoIP in the same conference Support for presentation (H.239/BFCP) from any participant at resolutions up to 3840 x 2160p5 Best Impression (automatic continuous presence layouts) Encryption and dual stream from any site 	
Protocols	H.323SIPCisco Webex	
Embedded encryption	 H.323 and SIP point-to-point Standards based: H.235 v3 and Advanced Encryption Standard (AES) Automatic key generation and exchange 	
IP network features	 DNS lookup for service configuration Differentiated services (DiffServ) (Quality of Service [QoS]) IP-adaptive bandwidth management (including flow control) Automatic gatekeeper discovery Dynamic playout and lip-sync buffering H.245 Dual-Tone Multifrequency (DTMF) tones in H.323 RFC 4733 DTMF tones in SIP Date and time support using Network Time Protocol (NTP) Media adaption and resilience Uniform Resource Identifier (URI) dialing Dynamic Host Configuration Protocol (DHCP) 802.1X network authentication 802.1Q Virtual LAN 802.1p (QoS and Class of Service [CoS]) 	
Call control	Native registration with Cisco Unified Communications Manager	

Specification	Description	
	 Requires CUCM Version 10.5.2 or later with device pack for Room Kit Plus Cisco Expressway Native registration with Expressway 	
IPv6 network support	 Single call stack support for both H.323 and SIP Dual-stack IPv4 and IPv6 for DHCP, Secure Shell (SSH), HTTP, HTTPS, DNS, DiffServ Support for both static and automatic IP configuration (stateless address auto configuration) 	
Security features	 Management using HTTPS and SSH IP administration password Menu administration password Disable IP services Network settings protection 	
Certificate management	 Certificate Authority Proxy Function (CAPF) support for additional security Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) X.509 Digital Certificates (DER encoded binary); both DER and Base-64 formats are acceptable for the client and server certificates; certificates with a key size of 1024, 2048, and 4096 are supported 	
Network interfaces codec medium	 One Ethernet (RJ-45) 10/100/1000 for LAN One Ethernet (RJ-45) 10/100/1000 for direct pairing with camera One Ethernet (RJ-45) 10/100/1000 with Power over Ethernet (PoE) for direct pairing with Touch 10 Wi-Fi 802.11a/b/g/n/ac 2.4 GHz/5 GHz for LAN. 2x2 MIMO 	
Other interfaces	• USB 2.0 port, uUSB, factory reset pinhole	
Power supplies (2)	 100 to 240VAC, 50/60 Hz, 12VDC input Average 20W, peak 70W 	
Operating temperature and humidity	 o°C to 35°C (32°F to 95°F) ambient temperature 10% to 90% Relative Humidity (RH) 	
Storage and transport temperature	• -20°C to 60°C (-4°F to 140°F) at 10% to 90% RH (noncondensing)	
Locking mechanism	Kensington security lock	
Dimensions	• Codec Plus: • Width: 14.1 in. (35.9 cm) • Height: 1.7 in. (4.3 cm) • Depth: 5.6 in. (14.3 cm)	

Specification	Description
	∘ Weight: 3.9 lb. (1.77 kg)
	Precision 6o Camera:
	∘ Length: 10.6 in. (26.8 cm)
	• Height (at max. tilt): 7.1 in (18 cm)
	∘ Depth: 6.4 in. (16.3 cm)
	• Weight: 5.5 lb. (2.5 kg)
Camera overview	• 1920 x 1080 at 60 fps resolution
	• Zoom
	∘ 1ox optical zoom
	∘ 2x digital zoom
	∘ 20x total zoom
	Pan and tilt
	Pan range: +/- 100 degrees
	∘ Tilt range: +/- 20 degrees
	• Field of view (FoV)
	Horizontal FoV: 8o degrees
	∘ Vertical FoV: 48.8 degrees
	• 1.0 m to infinity (wide) focus distance
	• F-value: 1.5
	Camera control: Ethernet
	Focus, white balance, and brightness: Automatic or manual
	Video interfaces
	∘ HDMI 1.4
	∘ 3G-SDI
	• Power
	° 12V/3A
	° 100-120/200-240VAC, 50/60 Hz
	Network interfaces: One LAN/Ethernet (RJ-45) 10/100 Mbit

Regulatory compliance

- Directive 2014/35/EU (Low-Voltage Directive)
- Directive 2014/30/EU (EMC Directive) Class A
- Directive 2014/53/EU (Radio Equipment Directive)
- Directive 2011/65/EU (RoHS)
- Directive 2002/96/EC (WEEE)
- NRTL approved (Product Safety)
- FCC CFR 47 Part 15B (EMC) Class A

Please check the Product Approval Status Database at https://www.ciscofax.com/ for approval documents per country.

Ordering information

To place an order, please contact your local Cisco representative and refer to Table 2.

 Table 2.
 Ordering information

Product name	Part number	Compliance model number
Cisco Webex Room Kit Plus Precision 6o – Upfront pricing (GPL*) • Cisco Webex Codec Plus • Cisco Touch 10 Control Unit • Cisco Precision 6o Camera	CS-KITP60-K9 CS-CODEC-PLUS+ CTS-CTRL-DVX-10 CTS-CAM-P60+	TTC7-25 TTC5-09 TTC8-07
Cisco Webex Room Kit Plus Precision 6o – NO RADIO Cisco Webex Codec Plus – NO RADIO Cisco Touch 10 Control Unit Cisco Precision 6o Camera	CS-KITP60-NR-K9 CS-CODEC-PLUS-NR+ CTS-CTRL-DVX-10 CTS-CAM-P60+	TTC7-25 TTC5-09 TTC8-07
Cisco Webex Room Kit Plus Precision 6o – NO CRYPTO Cisco Webex Codec Plus Cisco Touch 10 Control Unit Cisco Precision 6o Camera	CS-KITP60-K7 CS-CODEC-PL-NR-K7+ CTS-CTRL-DVX-10 CTS-CAM-P60+	TTC ₇ -2 ₅ TTC ₅ -0 ₉ TTC8-0 ₇
Cisco Webex Room Kit Plus Precision 6o – TAA compliant Cisco Webex Codec Plus – TAA, NO RADIO, or Cisco Webex Codec Plus – TAA Cisco Touch 10 Control Unit Cisco Precision 6o Camera	CS-KITP60-K9++ CS-CODEC-PLUS-NR++ CS-CODEC-PLUS++ CTS-CTRL-DVX-10 CTS-CAM-P60+	TTC7-25 TTC7-25 TTC5-09 TTC8-07
Options		
Cisco Table Microphone 20	CTS-MIC-TABL20	
Extension cable for Table Microphone 20	CAB-MIC-T20EXT	
Cisco Ceiling Microphone	CTS-MIC-CLNG-G2	
Shielded cable for ceiling mic (non-plenum rated)	CAB-ETHRSHLD-10M	
Wall mount kit for Codec Plus	CS-KITPLUS-WMK	
8 m HDMI 2.0 certified cable	CAB-PRES-2HDMI-GR	
HDMI 2.0 cable 1.5 m/5 ft, gray	CAB-2HDMI-1.5M-GR	
HDMI 2.0 cable 3 m/10 ft, gray	CAB-2HDMI-3M-GR	
Ethernet cable 1.5 m/5 ft, gray	CAB-ETH-1.5M-GR	
Ethernet cable 3 m/10 ft, gray	CAB-ETH-3M-GR	
Ethernet cable 5 m/16.4 ft, gray	CAB-ETH-5M-GR	
Software options – ordered separately		
Remote Monitoring	L-ROOM-RM (L-TP-RM)	
MultiSite (embedded multipoint)	L-KITPLUS-MS (L-ROOM-PAK)	
Spares		

Product name	Part number	Compliance model number
Cisco Webex Codec Plus	CS-CODEC-PLUS=	TTC7-25
Cisco Webex Codec Plus – no radio, no crypto	CS-CODEC-PL-NR-K7=	TTC7-25
Cisco Webex Codec Plus – no radio	CS-CODEC-PLUS-NR=	TTC7-25
Power supply 12VDC 70W	PSU-12VDC-70W-GR=	
Cisco Precision 6o Camera	CTS-CAM-P6o=	TTC8-07

^{**} GPL = Global Price List

Warranty information

Cisco Webex Room Kit Plus Precision 60 Integrator Package has a 90-day limited liability warranty.

Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's <u>Corporate Social Responsibility</u> (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	<u>Materials</u>
Information on electronic waste laws and regulations, including products, batteries, and packaging	WEEE compliance

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Services and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco collaboration investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, please visit https://www.cisco.com/go/collaborationservices.

Cisco Capital

Flexible payment solutions to help you achieve your objectives.

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. <u>Learn more</u>.

For more information

- Learn more about Cisco Webex Room Kit Plus.
- Learn more about Cisco Precision Cameras.
- Download the <u>Cisco Webex app</u>.

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-739532-06 10/19